

Appl. No. 10/605,653
Amdt. dated May 02, 2005
Reply to Office action of February 24, 2005

Amendments to the Specification:

1. Please substitute the line 2, paragraph 19 on page 7 with the following amended paragraph:

Moreover, the point light source generators 54 are aligned in an array
5 on a printed circuit board (PCB, not shown), or aligned in an array under
the diffusing plate 56 by means of a transparent carrier accompanied by a
~~by a~~ proper circuit arrangement. The backlight module 50 can further
include a reflecting plate (not shown) installed under the point light
source generators 54 for reflecting the light generated by the point light
10 source generators 54 to increase the efficiency of light source generators
54.

2. Please substitute the line 11, paragraph 21 on page 8 with the following amended paragraph:

Please refer to Fig.4 and Fig.5 showing respectively the structures of the
15 backlight modules 81 and 82 according to the second and the third
embodiment of the present invention. The difference from the first
embodiment is that the shape of scattering apertures 67 and 68 on the
surface of the diffusing plate 56 is rectangular (as shown in Fig.4) and
trapezoidal (as shown in Fig.5) respectively. The scattering apertures 66,
20 67, and ~~68~~ 68 are for scattering the light generated by the point light
source generators 54 uniformly, and can be designed differently according
to the scattering performance and is not limited to the shapes mentioned
above. Moreover, the inner walls of the scattering apertures 66, 67, and 68
can further include the scattering patterns (not shown) mentioned above to
25 increase the performance on scattering.